

## TECHNICAL DATA

			1254x40	2104x60	2606x90	3104x90	3106x120	3108x160	3110x200	3112x240	3116x300	3120x440	4106x160	4108x200	4110x240	4112x300
Capacity		kN	400	600	900	900	1200	1600	2000	2400	3000	4400	1600	2000	2400	3000
Motor Output		kW	4	5,5	7.5	7.5	11	15	19	22	22	30	15	18,5	22	22
Oil Tank Volume		Lt	80	140	140	140	140	210	210	210	280	450	210	210	210	280
Speeds (mm/s)	Approach		160	150	150	160	160	160	150	130	110	80	170	160	150	120
	Working		10	10	10	10	10	10	10	10	8	8	10	10	10	8
	Return		130	130	130	130	130	130	130	120	100	70	120	110	100	90
Approx. Weight		Ton	3.3	5.4	7.1	7.9	8.4	9.7	10	11	15	22	12	12.5	14	18.5
Bending Length	A	mm	1250	2100	2600	3100	3100	3100	3100	3100	3100	3100	4100	4100	4100	4100
Inside Frames	B	mm	1070	1600	2050	2550	2550	2550	2550	2550	2550	2550	3550	3550	3550	3550
Side Frame Width	C	mm	1470	1580	1580	1590	1590	1600	1600	1610	1815	2060	1600	1600	1610	1820
Bed Height	G	mm	800	880	880	880	880	880	880	880	905	1005	880	880	880	980
Daylight Opening	K	mm	455	475	540	530	540	540	530	530	660	575	530	530	530	635
Stroke	L	mm	215	210	260	260	260	260	260	260	320	320	260	260	260	320
Table Width	M	mm	60	60	60	60	60	60	90	90	380	450	60	90	90	280
Throat Gap	N	mm	410	410	410	410	410	410	410	410	500	500	410	410	410	500

- Design and specifications are subject to change without notice