

# L-1860 CONVENTIONAL LATHE

## *Technical Characteristics*

### Headstock

Speed range	25 - 2000 (12 changes) rpm.
Spindle nose:	D1-6
Spindle bore diameter	58 mm.
Horizontal taper of spindle	MT-6

### Capacity

Distance between centres	1500 mm.
Swing over bed	460 mm.
Swing over cross slide	270 mm.
Bed width	300 mm.
Centres height	230 mm.
Max. Section of Tool	25 x 25 mm.
Max. Travel of Cross Slide	285 mm.
Max. Travel of Compound Rest	128 mm.

### Power

Main motor	7,5 HP
------------	--------

### Feedrates

Leadscrew Pitch	Ø35x4 TPI. ó pulgada x 6 mm.
-----------------	------------------------------

Threads Imperial pitches	2 a 112 (60 kinds) TPI
Threads Metric pitches	0,1 a 14 (41 kinds) mm.
Threads Diametrical pitches	4 a 112 (50 kinds) DP
Threads Module pitches	0,1 a 7 (34 kinds) MP
Longitudinal Feeds Range	0,031 a 1,7 (42 kinds) mm/rev.
Cross Feeds Range	0,014 a 0,784 (42 kinds) mm/rev.

## Tailstock

Quill taper size	MT4
Quill diameter	60 mm.
Quill travel	130 mm.

## Weight & dimensions

Weight	1810 - 2115 Kg.
Dimensions	2750 x 1080 x 1340 mm.
Brand:	Travis